Pro Components

TB260 SERIES

TB260 * * TB260 * * 1
Pitch=5.0mm Pitch=10.0mm



SPECIFICATIONS

Pitch	5.0 mm, 10.0 mm
Wire range	14 AWG to 24 AWG
NO. of pole per Block	2 or 3
Rated	16 Amp,300 VAC
Housing	Polyamide 66,Blue
Terminals	Tin plated over Zinc Alloy
Screws	M2.6 x 0.45P,Yellow Chromated Zinc plated over Steel
Wire protector	Stainless Steel

mm to inch **NUMBER OF POLE 02~30

mm	0.6	1	1.1	3	3.5	3.6	5	7.5	8	10	11	20			
inch	0.024	0.039	0.043	0.118	0.138	0.142	0.197	0.295	0.315	0.394	0.433	0.787			

FEATURES

- Easy to assemble for any number of positions.
- End stackable without any loss of P.C.B. space.
- Special wire protector design to ensure reliable wire clamping.
- UL 94V-0 fire retardant engineering plastic used for the housing.
- Be capable of clamping a wide range of wire diameters.
- Compact size for P.C.B.

PART NUMBERING SYSTEM

```
TB   260 02  0  X  X  XX
 |    |   |  |  |  |   |
 |    |   |  |  |  |   +-------- Special number
 |    |   |  |  |  +------- Screw type:
 |    |   |  |  |           0:"+" screw
 |    |   |  |  |           1:"-" screw
 |    |   |  |  +------- Housing color:
 |    |   |  |           B:Bule, G:Green,
 |    |   |  |           K:Black
 |    |   |  +------ Pitch:
 |    |   |           0:Standard pitch
 |    |   |           1:Standard pitch×2
 |    |   +----- Number of pins
 |    +---- Series: Dimensions and rated
 +--- Model
```